


# GALAXY EXR300 E-3/L-3



Galaxy EXR300 E-3/L-3 features a new non-directional tread designed with deep, aggressive shoulder lugs that deliver superior traction. Its wide center lugs provide excellent ground contact for long wear, maximum stability and ride comfort.



OFF ROAD SURFACE MINING

## LOADER



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
14.00-25	TT	20	10	1368	375	4065	628	8500	7	10
				53.9	14.8	160	24.7	18700	102	5
14.00-25	TL	28	10	1368	375	4065	628	10,000	9.25	10
				53.9	14.8	160	24.7	22,000	135	5
15.5-25	TL	12	12/1.3	1278	394	3754	575	5600	4	10
				50.3	15.5	147.8	22.6	12300	58	5
17.5-25	TL	16	14.00 X 25	1348	445	4090	614	7300	4.75	10
				53.07	17.52	161	24.17	16100	69	5
17.5-25	TL	20	14.00 X 25	1348	445	4090	614	8250	5.75	10
				53.07	17.52	161	24.17	18200	83	5
17.5-25	TT	20*	-----UNDER DEVELOPMENT-----							
17.5-25	TL	24	14.00 X 25	1348	445	4090	614	9250	7.24	10
				53.07	17.52	161	24.17	20393	105	5
20.5-25	TL	16	17/2.0	1493	521	4304	65.9	8250	3.50	10
				58.8	20.5	169.4	25.2	18200	51	5
20.5-25	TL	20	17.00/2.0	1493	521	4304	65.9	9500	4.50	10
				58.8	20.5	169.4	25.2	20900	65	5
20.5-25	TL	24	17.00/2.0	1493	521	4304	65.9	10297	5.24	10
				58.8	20.5	169.4	25.2	22700	76	5
23.5-25	TL	20	19.5/2.5	1617	597	4605	705	10900	3.75	10
				63.7	23.5	181	27.8	24000	54	5
23.5-25	TL	28	19.5x25	1617	597	4605	705	13600	5.50	10
				63.7	23.5	181	27.8	30000	80	5
26.5-25	TL	28	22.00/3.0	1740	673	4900	750	15500	4.75	10
				68.5	26.5	193	29.5	34200	69	5
29.5-25	TL	28	25	1874	749	5202	789	17500	4.25	10
				73.8	29.5	204.8	31.1	38600	62	5

## EARTHMOVER

Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
14.00-24	TT	28	10	1360	370	4065	628	10000	9.25	50
				53.5	14.6	160	24.7	22000	135	30
14.00-24	TL	28	10	1360	370	4065	628	5600	6.50	50
				53.5	14.6	160	24.7	12346	94.3	30
14.00-25	TT	20	10	1368	375	4065	628	8482	7	50
				53.9	14.8	160	24.7	18700	102	30
15.5-25	TL	12	12/1.3	1278	394	3754	575	3243	2.48	50
				50.3	15.5	147.8	22.6	7150	36	30
17.5-25	TL	16	14.00 X 25	1348	445	4090	614	4241	3.03	50
				53.07	17.52	161	24.17	9350	44	30
17.5-25	TL	20	14.00 X 25	1348	445	4090	614	4990	5.75	50
				53.07	17.52	161	24.17	11000	58	30
17.5-25	TL	24	14.00 X 25	1348	445	4090	614	5600	4.76	50
				53.07	17.52	161	24.17	12346	69	30

Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
20.5-25	TL	16	17/2.0	1493	521	4304	659	5443	2.76	50
				58.8	20.5	169.4	25.2	12000	40	30
20.5-25	TL	20	17.00/2.0	1493	521	4304	659	5987	3.24	50
				58.8	20.5	169.4	25.2	13200	47	30
20.5-25	TL	24	17/2.0	1493	521	4304	659	7983	3.52	50
				58.8	20.5	169.4	25.2	17600	51	30
23.5-25	TL	20	19.5/2.5	1617	597	4605	705	10900	3.75	50
				63.7	23.5	181	27.8	24000	54	30
23.5-25	TL	28	19.5x25	1617	597	4605	705	8754	4	50
				63.7	23.5	181	27.8	19300	58	30
26.5-25	TL	28	22.00/3.0	1740	673	4900	750	9979	3.52	50
				68.5	26.5	193	29.5	22000	51	30
29.5-25	TL	28	25	1874	749	5202	789	17500	4.25	50
				73.8	29.5	204.8	31.1	38600	62	30