

GALAXY XD 2010 **R-4**



The Galaxy XD 2010 has a solid centre for long wear on hard surfaces. Its open, deep shoulders provide excellent traction in off-road conditions. The tire is made with highly abrasion resistant tread compound. The XD 2010 features a rim shield protector, heavy sidewall and a neutral contour casing.



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
5.70-12*				-----UNDER DEVELOPMENT -----						
23X8.50-12	TL	8	7	574	213	1675	260	955	4.5	10
				22.6	8.4	65.9	10.2	2105	65	6
23X8.50-12	TL	12	7JA	574	213	1675	260	1250	6.9	10
				22.6	8.4	65.9	10.2	2756	100	6
27X8.50-15NHS	TL	8	7	679	213	2023	314	1320	4.15	10
				26.7	8.4	79.64	12.4	2910	60	6
27X10.50-15NHS	TL	8	8	691	259	2055	319	1397	4.15	10
				27.2	10.2	80.9	12.6	3080	60	6
10x16.5	TL	8	8.25	770	254	2286	356	1900	3.5	10
				30.3	10.0	90.0	14.0	4189	51	5
10x16.5	TL	10	8.25	770	254	2286	356	2180	5.2	10
				30.3	10.0	90.0	14.0	4806	75	5
12x16.5	TL	8	9.75	820	295	2464	381	2180	3.4	10
				32.5	11.9	97	15.1	4806	49	6
12x16.5	TL	10	9.75	820	295	2464	381	2540	4.5	10
				32.3	11.6	97.0	15.0	5600	65	6
12x16.5	TL	12	9.75	820	295	2464	381	2865	5.5	10
				32.3	11.6	97.0	15.0	6316	80	6
33x15.50-16.5	TL	14	12	838	394	2429	377	3390	4.85	10
				33	15.5	95.6	14.8	7474	70	5
14-17.5NHS	TL	10	10.5	921	349	2771	420	3105	3.8	10
				36.3	13.7	109.1	16.5	6845	55	6
14-17.5NHS	TL	14	10.5	921	349	2771	420	3875	5.5	10
				36.3	13.7	109.1	16.5	8543	80	6
15-19.5NHS	TL	14	11.75	1019	389	3068	465	4565	4.8	10
				40.1	15.3	120.8	18.3	10064	70	6