



APOLLO AWL 822 29.5-25 28PR L5 26.5-25 28PR L5 23.5-25 20PR L5





APOLLO AWL 822

Superior Performance for Non Stop Operations

- Stiffer nylon casing for withstanding heavy loads and maintaining structural integrity of the tyre
- Premium grade compounds to enhance cut, chip and abrasion resistance

Long Life for highest return on investment

- Specially designed tread pattern with tie bar preventing lug shuffling
- · Shoulder guards and stiff sidewall to prevent damage and abrasion to sidewalls

Designed for Reliability

- Tapered groove with stone ejector to avoid carcass penetration
- Strong bead to ensure firm sitting on the rim for maximizing torque delivery

SIZE	PR	TRA CODE	PRODUCT NAME	LOAD INDEX	RIM SIZE	LOAD CARRYING CAPACITY (KG)	Inflation Pressure		OD (MM)	SW (MM)
							KPA	PSI	OD (MM)	SW (Min)
23.5-25.	20	L5 (2	AWL822	191A2	19.5x2.5-25	10900	375	54	1673	597
26.5-25	28	L5	AWL822	203A2	22.00x3-25	15500	475	69	1798	673
29.5-25	28	L5	AWL822	207A2	25.00x3.5-25	17500	425	62	1908	750

