

# PRIMEX G3000 G-2



Primex G3000 is specifically designed to meet the requirements of telehandlers. Engineered with a reinforced carcass, the G3000 provides improved stability that telehandlers require. The G3000's aggressive, open shoulder lugs deliver exceptional traction in off-road applications.



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
13.00-24	TL	12	8TG	1273	348	3835	582	5579	4.5	8
				50.1	13.7	151.0	22.9	12300	65	5
13.00-24	TL	16	8TG	1273	348	3835	582	6486	6	8
				50.1	13.7	151.0	22.9	14299	87	5
14.00-24	TL	12	8TG	1331	378	3810	612	6305	4.25	10
				52.4	14.9	150.0	24.1	13900	62	5
14.00-24	TL	16	8TG	1331	378	3810	612	7303	5.5	10
				52.4	14.9	150.0	24.1	16100	80	5

# PRIMEX G3000 HD L-2/G-2

Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
14.00-24	TT	16	8TG	1320	388	3955	598	3650	3.5	40
				52	15.3	155.7	23.5	8047	51	25
14.00-24	TL	16	8TG	1320	388	3955	598	3650	3.5	40
				52	15.3	155.7	23.5	8047	51	25