GALAXY ROCK MAX E-4/L-4





Galaxy Rock Max is designed especially for heavy duty surface mining applications. Robust nylon carcass with higher number of actual plies, provide superior strength to the carcass. A specially formulated tread compound for mining and extra wide reinforced bead provide greater strength. Wide & flat tread profile results in larger ground contact, higher stability, load carrying and traction.



Size	Туре	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg Ibs	bar psi	kmph mph
12.00-24	TT	20	8.50 X 24	1275	315	3870	600	3875	7.9	80
				50.2	12.4	152.4	23.6	8543	115	50
18.00-25	TL	40	13	1670	500	4915	727	9750	7	50
				65.7	19.7	193.5	28.6	21495	102	30
18.00-25	TL	32	13	1670.0	500.0	4915.0	727.0	8750	5.75	50
				65.7	19.7	193.5	28.6	19300	83	30
18.00-33	TL	40	13	1870.0	500.0	5535.0	860.0	11200	7	50
				73.6	19.7	218.0	33.8	24692	102	30
24.00-35	TL	48	17	2186.0	638.0	6470.0	1005.0	18500	6.5	50
				86.1	25.1	254.7	39.6	40785	94	30