

GALAXY SMOOTH COMPACTOR



SPECIAL
COMPOUND



COMPACTOR

Galaxy Smooth Compactor is specifically designed for compacting roadbeds and rolling asphalt. The smooth wide tread provides even pressure distribution on road surfaces. The compound used in this tire provides enhanced resistance to oily chemicals used in compacting applications. The Smooth Compactor tires have won the favor of major Original Equipment Manufacturers due to their outstanding durability.



ASPHALT SURFACE



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
7.50-15	TL	6	6	775	216	2337	353	1851	4	8
				30.5	8.5	92	13.9	4081	58	5
7.50-15 NHS	TT	12	6	780	208	2337	350	2120	7.5	16
				30.7	8.2	92	13.8	4674	109	10
7.50-15 NHS	TT	14	6	780	208	2255	350	2320	8.75	16
				30.7	8.2	88.8	13.8	5115	127	10
11.00-20	TT	18	8	1085	300	3180	498	5806	8.3	8
				42.7	11.8	125.2	19.6	12800	120	5
13/80-20*	TT	18		-----UNDER DEVELOPMENT-----						
14/70-20	TL	12	11	960.1	373.4	2943.9	447	4128	4.5	8
				37.8	14.7	115.9	17.6	9101	65	5
14/70-20	TL	20	11	960.1	373.4	2943.9	447	5443	7.6	8
				37.8	14.7	115.9	17.6	12000	110	5
23.1-26	TL	10	20	1575	587	4717	719	3878	1.4	8
				62	23.1	185.7	28.3	8550	20	5