

GALAXY SUPER GRIP E-3



SPECIAL
COMPOUND




HEAT
RESISTANT
COMPOUND



WEAR
RESISTANT
COMPOUND



Robust nylon casing with high number of actual plies provides excellent stability. It is an all purpose tire suitable for port and other industrial applications. Special tread compound provides long life when used on abrasive surfaces commonly found in ports. High ground contact area gives good traction on paved surfaces and continuous lug patterns, which help to reduce the chances of lug chunking and tire damage resulting in high life of tire. High turn up around bead, which results in less flexing at the bead area, which protect the bead ; minimizes the chances of bead failure. Tread design provides large ground contact area, to ensure that the pressure on the ground is less, resulting in more life and uniform wear.



HARD IMPROVED SURFACE



Size	Type	Rim Size in	Unloaded dimension		Static Loaded Radius	RC	PR	Inflated Pressure (bar psi)	Load carrying capacity for Loader application kg (lbs) Speed, kmph (mph)						
			OD	SW					25	20	15	10	5	Creep	Static
			mm	mm	mm	mm									
18.00-25	TL	13/2.5	1618	498	727	4915	40	10	21900	22200	22800	23600	25400	28000	31500
			63.7	19.6	28.6	193.5			145	48281	48943	50265	52029	55997	61729